




CSS610-8G-2S+IN

Eight 1G Ethernet ports and two SFP+ ports for 10G fiber connectivity.
Portable, powerful and extremely cost-effective – this switch is an instant classic!

The only **\$99**
10G SFP+ switch
on the market!



8 x Gigabit
Ethernet ports



2x SFP+ for
10G fiber



Port-to-port forwarding



MAC
filtering



VLAN



PoE-in




Traffic
mirroring




Broadcast
storm control

Cloud Smart Switch 610-8G-2S+IN is our answer to the everlasting demand for more power in a small and simple package. It comes with the user-friendly SwOS Lite which is easy to configure from your web browser. It gives you all the basic functionality for a managed switch, and more: you can manage port-to-port forwarding, broadcast storm control, apply MAC filters, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.



With 8 x 1G Ethernet ports and 2 x 10G SFP+ ports this switch is the fastest device in this size and price category on the market!



Despite its compact size, this switch provides serious performance:

28
Gbps

Non-Blocking
throughput

56
Gbps

Switching
capacity

41.7
Mpps

Forwarding
rate

Specifications

Product code	CSS610-8G-2S+IN
Switch chip model	88E6193X
Number of 1GbE ports	8
Number of 10G SFP+ ports	2
Dimensions	200 x 167 x 46 mm
Operating system	SwOS Lite
Operating temperature	-20°C to +60°C

Powering

PoE-in	Passive PoE
PoE-in input Voltage	12-57 V
Number of DC inputs	2 (PoE-in, DC jack)
DC jack input Voltage	12-57 V
Power adapter nominal voltage	24 V
Power adapter nominal current	0.8 A
Max power consumption without attachments	5 W
Max power consumption	11 W

Certification & Approvals

Certification	CE, FCC, IC
---------------	-------------

Included parts



24 V 0.8 A
power adapter



K-48 fastening set



Rack ears