

CRS328-24P-4S+RM

CRS328-24P-4S+RM is a 28 independent port switch, it has 24 Gigabit Ethernet ports, which offer different power output options: Passive PoE, low voltage PoE, 802.3af/at (Type 1 “PoE” / Type 2 “PoE+”) with auto-sensing. The four SFP+ ports provide up to 10 Gbps connectivity options via either optical fiber or Ethernet modules (not included).

CRS328-24P-4S+RM comes in a 1U rackmount case with 100-240 V AC 500 W power supply built-in. The device consumes up to 44 W leaving guaranteed 450 W (3x150 W per every 8 Ethernet ports) to power your PoE devices. Each port can provide up to 30 W with high voltage, and 26 W with low voltage power output.

The device has a “Dual boot” feature that allows you to choose between two operating systems - RouterOS or SwOS. If you prefer to have a simplified operating system with only switch specific features, use SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings. All the feature set comes with our disruptive price, providing best price/performance on the market.

Switching features

- Non-blocking Layer 2 switching capacity
- 16K host table
- IEEE 802.1Q VLAN
- Supports up to 4K simultaneous VLANs
- Port isolation
- Port security
- Broadcast storm control
- Port mirroring of ingress/egress traffic
- STP / RSTP / MSTP
- Access Control List
- MikroTik neighbor discovery
- SNMP
- 10218-byte jumbo frames support
- IGMP snooping
- IEEE 802.3ad and static link aggregation

Quick specifications

- 24 Gigabit Ethernet ports
- 4 SFP+ ports
- RJ45 serial console port
- Non-Blocking throughput: 64 Gbps
- Switching capacity: 128 Gbps
- Forwarding rate: 95.2 Mpps
- Maximum power consumption: 44 W (without PoE devices connected)
- Supports PoE+ IEEE 802.3at/af and 26 V Passive PoE
- Temperature based fan control
- 1U rackmount
- Selectable power output per port (26 / 53 W)



Specifications

Product code	CRS328-24P-4S+RM
CPU	98DX3236 800 MHz
RAM	512 MB
RAM type	DDR3
Storage type	Flash
Storage size	16 MB
Switch chip model	98DX3236
10/100/1000 Ethernet ports	24
SFP+ cages	4
Operating system	SwOS / RouterOS (Dual boot)
Supported input voltage	100 - 240 V
Cooling type	2 fans
Dimensions	443 x 300 x 44 mm
Operating temperature	-20°C .. +60°C tested
Max power consumption	44 W
Serial port	RJ45
License level	5

